

CX-UHF0-L-C

300016-T

Marine and Land Based UHF Antenna. Tx/Rx. 220W
0 dBd. N-female. N239F. Packed in a tube.

This omnidirectional unity gain antenna is used for radio telephone systems, two-way business radios and many other UHF applications. The antenna is manufactured in premium quality materials in order to prevent galvanic corrosion. Radiating elements are made of copper. The antenna is manufactured using crimping technology giving the antenna a 4-5 times stronger build-up. The swivel nut N239F is included. The antenna is subject for improvement at all times. The antenna has the same rugged design as all other AC Antennas products thus it withstands harsh environmental conditions, both on sea and land.

Short description

| | |
|---------------|-----------------|
| Product group | UHF |
| Design | Coaxial dipole |
| Pattern | Omnidirectional |

Electrical specifications

| | |
|--------------------------|-------------------------------------------------|
| Frequency range [MHz] | A: 380.0-430.0 B :380.0-435.0 C: 375.0-435.0 |
| Bandwidth [MHz] | A: 50 B: 55 C: 60 |
| Nominal Impedance [Ohm] | 50 |
| Max. Input Power [Watt] | 220 |
| Gain [dBd/dBi/Marine dB] | 0 / 2.15 / 3 |
| VSWR | A: <1.5:1 B: <2.0:1 C: <2.5:1 |
| Polarisation | Vertical |
| DC Shorted | Yes |
| DC Grounded | Yes |
| Connector | N-Female |

Mechanical specifications

| | |
|----------------------------------------|-------------------------------------|
| Length [m/ft] | 0.81 / 2.66 |
| Sections | 1 |
| Weight [kg/lbs] | 0.45 / 1.00 |
| Survival Wind Speed [km/h / m/s / mph] | 200 / 55 / 124 |
| Wind Area [m2/ft2] | 0.0138 / 0.1486 |
| Wind Load @ 160km/h [N] | 20 |
| Material | Fibreglass |
| Colour | White |
| Operating Temperature Range [°C/°F] | -55 to +70 / -67 to +158 |
| Ingress Protection | IP68 |
| Thread | 1" 14TPI male / ISO 228/1-G1 female |
| Mounting | Swivel nut N239F included |



